


# WASHER EXTRACTORS

## TWE 60 · 110



### STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid or powder detergent in 3 or 6 compartment frontal dispenser
- Standard equipped for automatic soap dosing
- Drum and tub, as well as the entire cabinet made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection in the front for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" (TWE 60) or 4" (TWE 110) drain valve for fast evacuation and shorter cycles
- Accelerometer for perfect balancing
- High flow inlet valves for faster filling
- Water inlet hoses
- Steam inlet hose

### OPTIONS

- Dual heating (electric & steam) selectable through the control
- Forward tilting
- Extra inlet valve for soft water
- Pneumatic inlet valves for faster filling, standard on TWE 110
- Pneumatic steam valve on TWE 60, standard on TWE 110
- Second drain valve for water recovery
- Weighing cells to measure amount of linen and reduce the water, energy and detergent consumption accordingly
- Chemical hold signal

TOLON

# WASHER EXTRACTORS

## TWE 60 · 110

MODEL	UNIT	TWE 60	TWE 110	
Dry load	lb	132	242	
Performance	lb/h	198	363	
Cycle time	min	30-45	30-45	
<b>DRUM</b>				
Drum diameter	inches	43.3	51.2	
Drum depth	inches	24	32.7	
Drum volume	ft <sup>3</sup>	20.4	38.9	
Wash speed	rpm	34	29	
Extraction speed	rpm	766	705	
G-force		360	360	
<b>DOOR</b>				
Door opening Ø	inches	21.7	26.6	
<b>HEATING</b>				
Electric	kW	30	60	
Steam	psi	58-87	58-87	
<b>ELECTRIC</b>				
Electric consumption*	kWh	26.25	52.50	
Motor	HP	14.75	29.49	
<b>STEAM</b>				
Steam valve connection Ø	DN-BSP	25-1"	40-1½"	
Steam pressure	psi	58-87	58-87	
Steam consumption	lb/cycle	61.6	110	
<b>AIR</b>				
Air connection Ø	inches	optional / 0.39	0.39	
<b>WATER</b>				
Inlet valve connection Ø	DN-BSP	2 x 25-1"	2 x 50-2"	
Water inlet (detergent) Ø	DN-BSP	1 x 25-1"	1 x 25-1"	
Water pressure	psi	29-58	29-58	
Water flow	gal/min	42.3	143	
Water consumption*	cold	gal/cycle	46.2	81.8
	hot	gal/cycle	61.2	104.3
Drain valve connection Ø (outer)	inches	3	4	
Drain flow	gal/min	60.7	158.4	
<b>PROGRAMMABLE CONTROL</b>				
16 default programmes (max. 99)		Std	Std	
7" colour, high-resolution LCD		Std	Std	
<b>DIMENSIONS (WxDxH)</b>				
Standard	inches	68.7x 68.9 x 75.2	75.2 x 80.3 x 81.1	
Tilting	inches	71.9 x 63.2 x 81.5	78.3 x 80.3 x 88.4	
Packing standard	inches	74.8 x 65.0 x 81.1	78.7 x 84.6 x 86.6	
Packing tilting	inches	74.8 x 68.9 x 87.4	80.7 x 90.6 x 94.5	
<b>WEIGHT</b>				
Net standard	lb	4235	8690	
Net tilting	lb	4730	8855	
Gross standard	lb	4400	9042	
Gross tilting	lb	4895	9207	
<b>SOUND LEVEL</b>				
	db(A)	67-77	70-77	

\* Consumption figures based on 'Eco 60°C' program (main wash, 2 rinses)

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding.

[www.tolon.com](http://www.tolon.com)

TOLON