COMBINATION STACK WASHER / DRYER

MLE22PRTGW / MLE22PDTGW

- Available as OPL and vended*

TURBOVENT® SYSTEM:

- Enables installation in long or complicated venting environments
- Helps improve component life
- High airflow helps reduce drying times for a wide variety of loads**

SPACE-SAVING CONFIGURATION:

- Full-capacity washer & dryer within the footprint of a single machine
- Console design lowers dryer height for easier loading and unloading

BUILT TO LAST:

- Premium bearings
- Robust hinges
- Blower guard, protects components to reduce service calls
- Durable soap dispenser is fully flushed with water during every wash cycle, helping minimize maintenance

* Coin drop selectors are not included with MLE/MLG22PDTGW models.
Coin box included as standard.
End user benefits
** Based on 11-lb load, 34 min. timed cycle, Heavy Soil

TOLON

COMBINATION STACK WASHER / DRYER

MLE22PRTGW / MLE22PDTGW

MODEL	UNIT (Imperial-Metric)	MLE22PRTGW / MLE22PDTGW
CAPACITY		
Washer Capacity	cu. ft. (liters)	3.1
Dryer Capacity	cu. ft. (liters)	6.7
IEC Capacity	lb. (kg)	23.2
NET DIMENSIONS		
Width	in.	27 (686)
Depth	in.	29.5 (751)
Height	in.	74 (1,880)
Door Opening	in.	14.25 (362)
Exhaust Duct Diameter	in.	4 (102)*
PACKED DIMENSIONS		
Packed Width	in. (mm)	29.25 (743)
Packed Depth	in. (mm)	34 (864)
Packed Height	in. (mm)	75.75 (1,924)
APPROXIMATE WEIGHT		
Packed	lb. (kg)	372 (169)
Net	lb. (kg)	372 (169)
ELECTRICAL REQUIREMENTS		
Voltage	V	240
Frequency	Hz	50
Breaker/Fuse	Amps	30
Airflow	CFM (CMM)	215 (6.10)
Electric Heating Element	watts	4,6

*Use 4" (100 mm) diameter rigid aluminum or galvanized steel duct.
Never use plastic, non-metal or combustible duct.

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding.
tolon.com